





P-LIGHT

ceiling light, LED, 6000K, IP65, rectangular, white, 6,5W

P-LIGHT suitable for use as emergency lighting for surface-mounted wall and ceiling lights. The safety lights are fitted with two built-in Ni-MH batteries with an automatic self-test and detection range of 30m. The emergency operating time of the luminaires is three hours. The luminaires can be operated permanently switched on / stand-by operation. The electrical connection is directly to the 230V supply. Other variants of the P-LIGHT series are available.



TECHNICAL DATA

Item no.:	240004
Number of different light outlets	1
Primary nominal voltage	220-240V ~50Hz mA/V
Width	37.5 cm
Height	17.6 cm
Depth	7.3 cm
Net weight	1.293 kg
Gross weight	1.438 kg
IP Code	IP 65
Safety class	II
Assembly	Surface
Assembly details	Ceiling, Wall
Wattage	6.5 W
Lumen	100 lm
Colour temperature	6000 Kelvin
Beam angle	110 °
Color	white
CRI	70
LXXBXX data	L70B50
BIG WHITE Page	341

Accessories

240009	PICTOGRAM FOILS , for P-LIGHT emergency exit light, set of 3, L/H 35.3/16.5 cm
240010	PICTOGRAM FOILS , for P-LIGHT emergency exit light, set of 2, L/H 35.3/16.5 cm
240022	RECHARGEABLE BATTERY , for P-LIGHT, 3.6V, 1000mA, set consists of 2 pieces