





## Vol Emergency ø135 mm


### 90-4880-14-OE

Downlight Vol Emergency ø135 mm 8.4W LED warm-white 3000K CRI 80 72.2° ON-OFF White IP54 847lm



### TECHNICAL FEATURES

IP54 IK08



Total power consumption of light (W) : 11.9W

Voltage / frequency : 220-240V/50-60Hz

Real lumens : 847

Dimming protocol : ON-OFF

Real lm/W : 71

Power Factor : 0.90

Correlated Colour Temperature (CCT) : LED warm-white 3000K

Useful life : 50.000h L80B20

Lens / reflector angle : FLOOD 72°

Warranty : 5 Years

Structure material : Aluminium

Structure finish : White



Diffuser material : Methacrylate

Diffuser finish : Opal



### LUMINOTECHNIC FEATURES

Lampholder	Quantity	Light source power (W)
LED	1	8.4W



### EMERGENCY MODULE FEATURES

Emergency equipment: 3H

Emergency lumens: 299

Auto-test function: NO

Driver voltage range: 230-240V/50-60Hz

Continuous/intermittent operation: Yes

Battery type: NiCd

### LOGISTICS

Net weight (kg): 1.4

Packaged weight (kg): 1.8

Packaging: -mm x -mm x -mm



