




## Max Small

## AI22-P3V9S10SZ5

Ceiling fixture IP66 Max Small LED 3.4W LED warm-white 2700K ON-OFF Urban grey 257lm



### TECHNICAL FEATURES

IP66 IK10



Total power consumption of light (W) : 4.2W

Real lumens : 257

Real lm/W : 61

Correlated Colour Temperature (CCT) : LED warm-white 2700K

UGR : <=16

Structure material : Aluminium

Structure finish : Urban grey

Diffuser material : Tempered glass

Diffuser finish : Transparent

Voltage / frequency : 220-240V/50-60Hz

Dimming protocol : ON-OFF

Power Factor : 0.40

Useful life : 50.000h L80B20

Warranty : 5 Years



Resistant to marine environments : Yes

Easily recycled luminaire

### LUMINOTECHNIC FEATURES

Lampholder	Quantity	Light source power (W)
LED	1	3.4W

UGR	
S=0.250	
Ceiling / cavity	0.7
Walls	0.5
Working Plane	0.2
Room dimensions	X=4H, Y=8H
UGR crosswise	9.9
UGR lengthwise	9.9



### LOGISTICS

Net weight (kg): 0.58

Packaged weight (kg): 0.71

Packaging: 180mm x 180mm x 70mm



20 Un

